

GoDEX® DT2x/DT4x/G500

Label Printer

Specifications

Print Speed:

DT2/DT4: up to 7 ips
G500: 5 ips

Print Length:

Minimum: 0.16 in
Maximum: 68 in

Print Width:

DT2: 2.12 in
DT4/G500: 4.25 in

Media:

Continuous form, gap labeling, black mark sensing and punched sensing
Label roll O.D. max: 5.0 in

Real Time Clock:

DT2/DT4: standard

Core:

1 in, 1.5 in
Thickness: 0.06 to 0.20 mm

Ribbon (G500):

Core: 1 in
Length: 300 m
Max ribbon roll O.D.: 2.67 in
Wide: 1.18 to 4.33 in

Printer Language:

GZPL or GEPL, EZ PL auto switch

Resident Fonts:

11 resident alphanumeric fonts (included OCR A and B) those are expandable eight times horizontally and vertically. All bit mapped fonts in eight orientations

Bar Codes:

Code 39, Code 93, Code 128 (subset A, B, C,) UCC/EAN - 128 K-Mart, UCC/EAN - 128, UPC A/E (add on 2 and 5,) 2 of 5, EAN 8/13 (add on 2 and 5,) Codabar, Post Net, EAN 128, DUN 14, MaxiCode, HIBC, Plessey, Random Weight, Telepen, FIM, China Postal Code, RPS 128, PDF 417, Datamatrix code, QR Code

Dimensions:

DT2: 8.58 L x 6.77 H x 3.94 in W (218 L x 172 H x 100 mm W)
DT4: 8.58 L x 6.53 H x 6.61 in W (218 L x 166 H x 168 mm W)
G500: 11.2 L x 6.8 H x 8.9 in W (285 L x 171 H x 226 mm W)

Interfaces:

Baud rate 4800 to 115,200; DB9
USB port U2.0 (B-type)
Ethernet (RJ-45)

Memory:

8 MB flash - DT2x, DT4x and G500

Power:

Auto switching 100/240VAC 50/60 Hz

Environment:

Operation: 41° F to 104° F (5° C to 40° C)
Storage: -4° F to 122° F (-20° C to 50° C)

Humidity:

Operation: 30 to 85 % non-condensing, free air
Storage: 10 to 90% non-condensing, free air

Approvals:

CE (EMC), FCC Class A, CB, CUL, CCC

Warranty:

Two-year limited warranty



APPROVALS



Standard Features

- Auto language emulations GEPL, GZPL
- Free GoLabel design software for EZPL
- 203 DPI (8 dot/mm)
- Drop in media loading
- USB or RS-232 interface
- Plain, gap label, black, mark or fanfold label
- Label length detection
- Direct thermal
- Model G500- direct thermal/thermal transfer
- 32 Bit CPU
- Serrated tear bar

GoDEX® DT2x/DT4x/G500

Label Printer

PRINTERS

Part Number/Price

PART #	DESCRIPTION	WEIGHT	PRICE
167515	DT2 2 in direct thermal, time and date 10/240VAC printer	2.65 lb	Consult
167516	DT4 4 in direct thermal, time and date 110/240VAC printer	3.3 lb	Consult
132425	G500 4 in direct/thermal transfer, 110/240VAC printer	6 lb	Consult
DT2x			
167626	Label peeler, black		Consult
167627	Cutter, black		Consult
150740	Print head		Consult
DT4x			
167628	Label peeler, black		Consult
167629	Cutter, black		Consult
150743	Print head		Consult
107638	Guardian enclosure		Consult
G500			
150744	Label peeler		Consult
150745	Cutter		Consult
150746	Print head		Consult
107639	Guardian enclosure		Consult
Cables For All Printers			
41276	6 ft serial cable DB9 M to blunt end, (Rice Lake indicators)		Consult
79074	USB cable		Consult
64661	6 ft serial cable DB9 M to 8-Pin DIN		Consult
64660	6 ft serial cable DB9 M to DB9 male		Consult
Custom Pin	Custom RS-232 serial cable		Consult

Options/Accessories

PART #	DESCRIPTION	PRICE
38941	Cleaning pen for open print head printers 12 per box	Consult
38794	Cleaning cards, 2 in W x 6 in L 25 per box for RL-22DT	Consult
35664	Cleaning cards, 4 in W x 6 in L for RL-42DT and RL-42TT	Consult
111085	Power supply, printers	Consult
Label Stock/Ribbon		
DT2x		
110347	Direct thermal, 2.25 W x 1.25 in L, 5 in diameter with perf., 2100/roll	Consult
40332	Direct thermal, 2.25 W x 2 in L, 5 in diameter with perf., 1445/roll	Consult
110348	Direct thermal, 2.25 W x 3 in L, 5 in diameter with perf., 950/roll	Consult
110349	Direct thermal, 2.25 W x 4 in L, 5 in diameter with perf., 700/roll	Consult
65617	Direct thermal, 2.25 W x 4.5 in L, 5 in diameter with perf., 600/roll	Consult
110346	Direct thermal, 1.20 in x 0.85 in L, 5 in diameter with perf., 2710/roll	Consult
47761	Direct thermal, 2.5 W x 121 ft L, continuous 12 rolls/case	Consult
DT4x		
53251	Direct thermal, 4 W x 3 in L, 5 in diameter with perf., 930/roll	Consult
40331	Direct thermal, 4 W x 4 in L, 5 in diameter with perf., 745/roll	Consult
37345	Direct thermal, 4 W x 6 in L, 5 in diameter with perf., 450/roll	Consult
G500		
53261	Thermal transfer, 4 W x 3 in L, 5 in diameter with perf., 930/roll	Consult
110536	Ribbon (black), 4.3 in wax/resin, 984 ft length	Consult
110537	Ribbon (black), 2.5 in wax/resin, 984 ft length	Consult

www.ricelake.com | Phone: 800-472-6703

RICE LAKE