

EZ-Desktop Printer

EZ Options



Easy Viewer



Stripper Module



Cutter Module



Label Stand



EZ 1000

plus series



ISO 9001:2000 CERTIFIED

GODEX

EZ1000 plus series Product Specifications

Model	EZ-1200 plus	EZ-1300 plus
Resolution	203 dpi (8 dot/mm)	300 dpi (12 dot/mm)
Print Mode	Thermal Transfer / Direct Thermal	
CPU	32 Bit	
Memory	4MB Flash, 8MB SDRAM	
Print Speed	2 IPS ~ 6 IPS	2 IPS ~ 4 IPS
Print Length	Min 12 mm (0.47") Max 1727 mm (68")	Min 12 mm (0.47") Max 762 mm (30")
Print Width	108 mm (4.25")	105.7 mm (4.16")
Sensor Type	Adjustable Reflective sensor; Fixed transmissive, center aligned	
Sensor Detection	Type : Label gap and black mark sensing Detection : Label length auto sensing and / or program command setting	
Media	Label Roll OD : Max. 125 mm (4.92") Core Diameter : 1", 1.5", 3" Width : 25 mm (1") ~ 118 mm (4.64") Thickness : 0.06 mm ~ 0.25 mm (0.0025 ~ 0.0098")	
Ribbon	Length : 300 M (981 ft) Max. Ribbon roll OD : 68 mm (2.67") Ribbon width : 30 mm ~ 110 mm (1.18" to 4.33") Coating : Outside only Core Inner Diameter : 25.4 mm (1")	
Printer Language	EZPL (Firmware downloadable)	
Software	Application : QLabel-IV (EZPL only) DLL & Driver : Microsoft Windows NT 4.0, 2000, XP and Vista	
Resident Fonts	11 resident alphanumeric fonts (included OCR A & B) , those are expandable 8 times horizontally and vertically. All bit mapped fonts in 8 orientations. Scalable Font (Code Page 850 & 852) in 4 orientations.	
Fonts Download	Windows bit mapped in 8 orientations. True Type font (Ver. 2.XX) and Asian fonts in 4 orientations.	
Image Handling	BMP, PCX, Support ICO, WMF, JPG, EMF file through software	
Barcodes	Code 39, Code 93, Code 128 (subset A, B, C) , UCC/EAN-128 K-Mart, UCC/EAN-128, UPC A / E (add on 2 & 5) , I 2 of 5, I 2 of 5 with Shipping Bearer Bars, EAN 8 / 13 (add on 2 & 5) , Codabar, Post NET, EAN 128, DUN 14, MaxiCode, HIBC, Plessey, Random Weight, Telepen, FIM, China Postal Code, RPS 128, PDF 417, Datamatrix code & QR code	
Interfaces	Serial port : RS-232 (Baud rate : 4800 ~ 115200, Xon / Xoff, DSR / DTR) USB port : V2.0 Parallel port : Bi-direction	
Control Panel	Two multiple-color LED lights : Ready, Status Function Key : FEED	
Power	Auto Switching 100/240 VAC, 50/60 Hz	
Environment	Operation : 40°F to 104°F (5°C to 40°C) Storage : -4°F to 122°F (-20°C to 50°C)	
Humidity	Operation : 30-85%, non-condensing. Free air Storage : 10-90%, non-condensing. Free air	
Cert. Approval	CE, FCC Class A, CCC, CB, cUL	
Printer Dimension	Length : 285 mm (11.2") / Height : 171 mm (6.8") Width : 226 mm (8.9") / Weight : 2.72 Kg	
Options	Rotary Cutter Module Stripper Module Compact Flash (CF) Card socket with Real time clock (RTC) Internal Ethernet Adapter Card	
Packing	USB cable, Power cord, Parallel cable, Ribbon, Ribbon Shaft (1"core) , Empty ribbon core, Label, Label roll core, CD, Quick Start Guide, Cleaning card	

Specifications are subject to change without notice.